



# Model A385

## Pneumatic Sealless Combination Steel Strapping Tool

### Standard Features

The high-performance tool with MicroLock™ sealless joint has been designed for stationary applications. It tensions, seals and separates the strap automatically by actuating the appropriate keypad. It is produced in different tensioning levels and can process regular duty and high tensile steel straps. The uniform tension of the straps is guaranteed by a pneumatic drive and the security sealless MicroLock™ joint guarantees perfectly secured goods.

### Specifications

Weight:	10.0 kg / 22.0 lbs. without suspension 10.5 kg / 23.2 lbs. with suspension
Suitable strap qualities:	95-200mm/3/8-3/4" wide 0.38-0.63mm/0.15-.025" thick
Tension:	The tool is available for four different stages of strap tension, see model listing for more information.
Suspension:	Suspension bracket for standard application is supplied with the tool

Item No.	Model	Strap widths		Thicknesses		Max. Tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/s	inch/s
13.7057	A385/16/0.58-0.63/4.7	16	5/8"	0.58-0.63	.020-.025	4700	1060	100	4.0
13.7052	A385/16/0.58-0.63/3.3	16	5/8"	0.58-0.63	.020-.025	3300	740	120	4.7
13.7061	A385/19/0.50-0.63/7.0	19	3/4"	0.50-0.63	.020-.025	7000	1570	65	2.5

