



MINI-MAX SERIES

Semi-Automatic Strapping Machines

Features

- 60 second warm up time
- Heavy-duty, hinged, stainless steel Top
- Straps virtually any size carton
- Easy strap loading
- Handles 6, 9, 12, and 15mm Strapping
- Portable
- Simply Designed

Specifications

- Automatically feeds, tensions and heat seals strap
- Adjustable to accommodate strap widths from 1/4" to 5/8"
- External tension control permits strap tension for delicate or solid bundles
- 60 second warm-up time for the heater blade
- Heavy-duty, hinged, stainless steel top
- Unit is mounted on locking casters for quick movement to packaging locations
- Energy-saving, adjustable timer switch, automatically shuts off motor when not in use
- CE safety standard design
- Reliable microprocessor (PLC) control
- Rigid caster with brake
- Precision die cast alloy seal head cam housing
- Straps virtually any size carton
- CE approved



OV102



OV101

| |
|--|
| Mini-Max Series |
| Semi-automatic Strapping Machines |
| Electrical Supply: 110 V, 60 HZ, Single Phase |
| Strapping Speed : 2.5 seconds per strap |
| Tension Range: 33 - 100 lbs |
| Standard Machine Size: 35.5" L x 22.8" W x 29.5" H |
| Net Weight: 220 lbs (Closed Cabinet) |
| Net Weight: 185 lbs (Open Cabinet) |